






COSSES A RIVER


Laiton





Traitement de surface standard : Sn Pb 60/40 3 à 5 µ sous-couche CU ou Ni 2 µ







	H	862	777	777/01	784	772	51	878	871/02	846	21	874
		sans trou		sans trou							long	
d1. mm		1,90	1,90	2,00	2,00	2,00	2,00	2,50	2,90	3,00	3,00	3,50
h .. mm		3,30	2,75	2,50	2,50	3,60	3,50	3,00	2,60	4,00	4,50	3,50
L .. mm		15,00	23,00	9,00	9,00	9,50	20,0	12,00	11,50	15,00	15,50	17,10
d2. mm		5,30	5,00	4,40	4,40	5,00	5,30	5,50	4,00	6,30	7,00	6,00
a .. mm		3,00	1,50	2,70	2,70	3,00	2,80	3,30	3,50	3,20	4,00	3,50
e .. mm		0,25	0,25	0,25	0,25	0,35	0,40	0,40	0,40	0,40	0,40	0,70
Standard			x	x		x		x			x	

		877	716/01	795	31		729	6 court	881		890
ø ou φ mm		1,70	2,00	2,80	2,80		2,50	3,70	2,50		2,00
h .. mm		3,50	3,60	3,20	3,60		2,90	3,60	2,60		2,50
L .. mm		11,0	15,00	12,00	15,00		18,10	24,50	8,10		18,00
d2. mm		3,00	6,50	5,50	6,20		5,00	6,30	5,00		5,00
a .. mm		3,00	3,50	3,30	3,40		3,00	3,50	3,00		3,00
e .. mm		0,40	0,40	0,40	0,40		0,40	0,40	0,40		0,40
Standard				x	x			x			



		34		891		718		869
φ mm		3,00		2,00		3,00		2,05
h .. mm		3,70		3,30		3,20		2,45
L .. mm		10,00		8,50		9,00		11,70
d2. mm		5,10		4,00		5,10		6,10
a .. mm		5,10		2,80				3,00
e .. mm		0,40		0,50		0,50		0,30
Standard		x						

	881 D		738 B		875	738	38	737		795 A		860
d1 ou c. mm	2,00		2,80		2,00	2,80	2,80	2,80		2,80		3,00
h .. mm	2,70		2,80		3,20	2,90	3,20	2,90		3,00		3,05
L .. mm	7,00		8,80		18,00	18,00	18,00	24,50		7,00		15,0
d2. mm	4,50		5,00		5,00	5,00	5,00	6,30		5,50		6,00
a .. mm	2,80		3,00		3,00	3,00	3,00	3,50		3,30		-
e .. mm	0,30		0,40		0,40	0,40	0,40	0,40		0,40		0,35
Standard	x		x				x			x		x

Cosses sans x sur la ligne standard : fabrication spéciale
(minimum par commande : 5000 pièces)